



Specializing in Research & Development of High Performance Pressure Sensitive Tapes

Product Data Sheet DC-1345

Product Description: Product DC-1345

Features/Benefits:

- -Highest quality foam for permanent bonding
- -Quick stick for bonding vinyl banners and for making pole pockets
- -Bonds permanently to variety of substrates (metal, wood, plastics etc.)
- -Requires a 72 set-up bond period

Physical Characteristics	Nominal Values
Total Tape Thickness	45 mils
Liner Type	Red Polyethylene
Carrier	Foamed Acrylic
Peel Adhesion (PSTC-1)	315 oz/in
Tensile Strength	36.3 lb/in
Temperature Resistance	Up to 320°F Short Term and 212°F Long Term
Cold Temperature Resistance	-22°F to 176°F (-30°C to 80°C)
Density	-40°F
Standard Length	36yds

Tape Application: To achieve ultimate bond strength please be sure materials being bonded are clean and free of dust, dirt, oil or other substances which can affect the bond of the tape adhesive. Firm application pressure will promote a strong, long lasting bond. Adhesive bond strength is dependent upon the material type being bonded. If a variety of materials are being used, please be sure to test the suitability of product performance with each material. Please contact Custom Adhesive Products at the phone number below with questions regarding your taping applications and needs.

Notice: Physical and performance values listed above are average values obtained from tests performed according to PSTC or ASTM standard test methods. Custom Adhesive Products does not make any warrant of any kind as to the results listed above. The information listed above does not represent a performance guarantee. Product performance may vary with each individual application and the purchaser should test the product prior to use and satisfy themselves regarding product functionality in their application. Custom Adhesive Products shall not be liable for damages in excess of the purchase price of its products or for incidental or consequential damages.

www.captape.com 2909 Wolff St. Racine, WI 53404
(Ph) 262-595-0568 (Toll Free) 866-440-8273 (Fax) 262-595-0566

Rev 7/06